



Capacity	30L	50L	80L	100L
SKUS	VME-WHT-V030	VME-WHT-V050	VME-WHT-V080	VME-WHT-V100
Installation	Vertical wall mounted	Vertical wall mounted	Vertical wall mounted	Vertical wall mounted
Control type	Manual Control	Manual Control	Manual Control	Manual Control
Heating power	Single	Single	Single	Single
Material of insulation layer	PUF	PUF	PUF	PUF
Thickness of insulation layer	25mm	25mm	25mm	25mm
Protective anode	Magnesium	Magnesium	Magnesium	Magnesium
Color of finishing	White	White	White	White
Heating element	INCOLOY 840	INCOLOY 840	INCOLOY 840	INCOLOY 840
Rated power	1500W	1500W	1500W	1500W
Rated voltage	230V	230V	230V	230V
Rated frequency	50Hz	50Hz	50Hz	50Hz
Rated current	6.8A	6.8A	6.8A	6.8A
Thermostat	Capillary	Capillary	Capillary	Capillary
Temperature range	30°C to 75°C	30°C to 75°C	30°C to 75°C	30°C to 75°C
Thermal cut-off	Capillary	Capillary	Capillary	Capillary
Protection against humidity	IPX4	IPX4	IPX4	IPX4
Working Pressure	0.8MPa	0.8MPa	0.8MPa	0.8MPa
Cable length	1400mm	1400mm	1400mm	1400mm
Product size (mm)	Vertical Φ 350×575	Vertical Φ 390×721	Vertical Φ 390×749	Vertical Φ 460×889
Carton size (mm)	Vertical 410×410×660	Vertical 465×465×785	Vertical 535×535×815	Vertical 545×545×945
Net weight (kg)	Vertical 14.20	Vertical 19.50	Vertical 23.50	Vertical 27.10
Gross weight (kg)	Vertical 16.00	Vertical 21.90	Vertical 25.00	Vertical 28.50
In box accessories	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1