





Available Color Finishing	& Gold Matt PVD (GMP)
	WRAS, ACS Approved (M 24X1) Black Chrome (BCH), Black Matt (BLM), Blush Gold Bright PVD (BGP), Gold Bright PVD (GBP)
Finish Aerator Size	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)
Power Source	6 Volt Battery - Duracel (4 *1.5V AA cell)
Adjustable Parameters	Detection Range : 100 - 300mm, default : 140-150mm,
Electronic Parameter Setting Procedure	Red button on Control Box
IP rating	Protection against intrusion (control box) IP 65 Protection against intrusion (sensor eye) IP 67
Solenoid Valve Specification	Operating pressure 1.0 - 5.0 bar Nominal Voltage : 6 Volt DC Low power consumption : Bi-stable pulse controlled
Material Composition Specification in Percentage	Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)
Recommended Water Pressure	1.0 Bar - 5.0 Bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Flow Rate	15.82 LPM @ 3 bar
Inlet Water Connection	1/2"BSP / 15mm
Water Temperature	Maximum 65 °C
Water Supply	Cold or premix water (1 inlet)
Description	Laguna High Neck Sensor Faucet for Wash Basin Deck mounted Complete with Control Box (Battery Operated)
Product code	SNR-CHR-91017

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.