



Product Code	OHS-CHR-1677
Description	Duoflo Shower Round Shape 450mm AISI 304 stainless steel with RGB LED light remote control & installation kit for false ceiling <ul style="list-style-type: none"> ▪ Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz • 2-functions <ul style="list-style-type: none"> ▪ Rain, ▪ Waterfall
Flow Rate	Rain - 49.87 LPM @ 3 bar Waterfall - 56.76 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Rain & Mist Functions
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm ³) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102
REMOTE CONTROL	<p>RGB Remote Control Remote Option : RGB Working Voltage: 3Vd c Wireless Frequency: 2.4GHz Working Temperature: -30C-55C</p>
LED POWER SUPPLY	<ul style="list-style-type: none"> • CHROMO THERAPY (RGB) • LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz • COLOR VARIATION • <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Mono Color (RGB)</p> </div> <div style="text-align: center;"> <p>Chromo Therapy</p> </div> </div> <p style="text-align: center;">LED On / Off Switch Sensor by Remote Control</p>
Technology	Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)
Available Finishing	Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP) & Gold Matt PVD (GMP)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	