


jaquar.com Document No. SNW/CNS/24/959NUF











TOP VIEW	SIDE VIEW	BACK VIEW
General Information		
Product Code	CNS-WHT-959NUF	
Brand	Jaquar	
Colour	White	
Туре	Wall Hung WC	
Material	Ceramic-Vitreous China (VC)	
Product Specification		
Product Dimension	380X545X375 mm	
Bowl Opening (Inner Dimension)	270x335 mm	
Product Net Weight	21 kg	
Product Gross Weight	25 kg	
Packaging Dimension	450x380x560mm	
Outlet	Horizontal	
Outlet Hole Dimension	External diameter of outlet hole dia. Ø 100 ± 5 mm	
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤	220 mm
Product Features	Rimless ,Regular, Dual & I Flush advantages. UF Soft Close Seat Cover,Complere Trap Glaze, Dual Flushing-3/6 LPF,Anti germ glaze.	
ACCESSORIES PROVIDED		
Seat Cover	CNS-WHT-115UF	
Inlet & Outlet gasket	ZPS-WHT-GK01	
ACCESSORIES RECOMMENDATION		
Rag bolt	ZPS-MST-RB07	
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS	

CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \neg Carefully inspect the new product for damage before installation.
- \neg Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- \neg Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product