



Product Code	OHS-CHR-1675	
Description	Duoflo Shower Round Shape 450mm AISI 304 stainless steel with I • Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SM • 2-functions • Rain, • 4 X Mist	
Flow Rate	Rain - 67.15 LPM @ 3 bar Mist - 8.94 LPM @ 3 bar	
Flow regulator	By using flow regulators + Brass Housing (Product should be order Bar pressure) one can regulate the flow rate.	red with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3
Recommended Water Pressure	1.0 Bar - 3.0 Bar	
Mount Type	Ceiling Mounting	
Spray Modes	Rain & Mist Functions	
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102	
REMOTE CONTROL	RGB Remote Control Remote Option : RGB Working Voltage: 3Vd c Wireless Frequency: 2.4GHz Working Temperature: -30C-55C	ON/OFF Image: Color +/+ Mode Key Image: Color +/+ Image: Color -/+ Image: Color +/+ <
LED POWER SUPPLY	CHROMO THERAPY (RGB) LED x 0.23W with 12V Power Supply (SMP AC 100-240V, 50-60Hz COLOR VARIATION • Mono Color (RGB)	PS) including Controller, connecting to Chromo Theraphy LED On / Off Switch Sensor by Remote Control
	Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.	
Technology		
Fechnology Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)	

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.