


jaquar.com Document No. SNW/LAS/24/955P180UFSM











RΔ	CK	V/I	EW

General Information			
	Lac Must programmers		
Product Code	LAS-WHT-91955P180UFSM		
Brand	Jaquar		
Colour	White		
Туре	Back To Wall WC		
Material	Ceramic-Vitreous China (VC)		
Product Specification			
Product Dimension	370x520x415 mm		
Bowl Opening (Inner Dimension)	275x335 mm		
Product Net Weight	33.2 kg		
Product Gross Weight	39.0 kg		
Packaging Dimension	410x420x535 mm		
Outlet	Horizontal		
Trap Distance	P Trap - 180 mm		
Inlet And Outlet Hole Dimension	Internal diameter of inlet hole dia. Ø 58 ± 3 mm		
	External diameter of outlet hole dia. Ø 100 ± 5 mm		
Product Features	Rimless WC slim seat cover, Blind Installation, Exclusive design, Dual Flush-3/6LPF, Anti germglaze.		
ACCESSORIES PROVIDED			
Seat Cover	LAS-WHT-91101UF		
fixing kit	ZPS -WHT-FB13		
Inlet Outlet Gasket	ZPS-WHT-GK01		
ACCESSORIES RECOMMENDATION			
Rag bolt	ZPS-SNS-RB07N		
Concealed cistern	JCS-WHT-2400,JCS-WHT-2400P,JCS-WHT-2400S,JCS-WHT-2431,JCS-WHT-2431P,JCS-WHT-2431S		

CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \neg Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ¬ Do not allow cleaners to sit or soak on the product.
- \lnot Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- \neg Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product