



Product Code	OHS-CHR-1787
Description	Multifunction 100mm dia Cylindrical Shape Overhead Shower with Normal, Massage & Mist Spray
Flow Rate	“Normal - 16.35 LPM @ 3 bar Massage - 12.25 LPM @ 3 bar Mist - 12.00 LPM @ 3 bar”
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Wall Mounting
Spray Modes	Normal, Massage and Mist functions
Material Composition Specification in Percentage	<p>“Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>ABS Specification Specific Gravity g/cm² (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa OC (78-102)”</p>
Technology	<p>“Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.</p> <p>Click Position System - One can feel and hear the click while changing the function of the shower sprays.”</p>
Finish	“Salt Spray (350 hrs + Validated) Adhesion (Pass)”
Available Finishing	CHROME (CHR)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	